

A Learning-Based Approach for Traffic State Reconstruction from Limited Data

Nail Baloul, Amaury Hayat, Thibault Liard, Pierre Lissy¹

PGMO Days, EDF Lab Paris-Saclay, Palaiseau


November, 19th 2025



ÉCOLE NATIONALE DES
PONTS
ET CHAUSSÉES



IP PARIS



¹N. Baloul, A. Hayat, and P. Lissy are with CERMICS, ENPC and T. Liard is with XLIM, Université de Limoges

Table of Contents

Introduction

Existing Traffic Flow Models

(Learning-Based) Optimization for Traffic Flow Reconstruction

Numerical experiments

Conclusion and Perspectives



Traffic jam in Beijing

- Traffic congestion impacts urban *mobility* and *environmental* quality



Traffic jam in Beijing

- ▶ Traffic management relies on **control** schemes to address perturbed traffic conditions
- ▶ Most existing control techniques require **complete** and **accurate** knowledge of state
- ▶ In practice, full information is rarely available due to **limited** and **noisy** measurements



Traffic jam in Beijing



Goal $\Rightarrow$ develop reliable methods for **estimating traffic from partial data**

Benchmark scales of traffic models

- ▶ **microscopic** $\Rightarrow$ **individual** vehicle dynamics, full information given

Microscopic model

- ▶ Simulation of **agent-based** dynamics
- ▶ Tracking position $x_i(t)$, velocity $v_i(t)$
- ▶ Each driver responds to **surrounding** traffic

$$\dot{v}_i(t) = F(v_i(t), x_i(t)) \quad (1)$$

Benchmark scales of traffic models

- ▶ **macroscopic** $\Rightarrow$ continuum representation using **aggregated** variables

Macroscopic model

- ▶ Traffic modelled as a **continuous** flow
- ▶ Density $\rho(t, x)$, speed $v(\rho)$, flux $f(\rho)$
- ▶ Total number of cars is **conserved**

$$0 = f(\rho(t, a)) - f(\rho(t, b)) = \frac{d}{dt} \int_a^b \rho(t, x) dx \quad (2)$$

Benchmark scales of traffic models

- ▶ **microscopic** $\Rightarrow$ **individual** vehicle dynamics, full information given
- ▶ **macroscopic** $\Rightarrow$ continuum representation using **aggregated** variables

Microscopic model

- ▶ Simulation of **agent-based** dynamics
- ▶ Tracking position $x_i(t)$, velocity $v_i(t)$
- ▶ Each driver responds to **surrounding** traffic

$$\dot{v}_i(t) = F(v_i(t), x_i(t)) \quad (1)$$

Macroscopic model

- ▶ Traffic modelled as a **continuous** flow
- ▶ Density $\rho(t, x)$, speed $v(\rho)$, flux $f(\rho)$
- ▶ Total number of cars is **conserved**

$$0 = f(\rho(t, a)) - f(\rho(t, b)) = \frac{d}{dt} \int_a^b \rho(t, x) dx \quad (2)$$

- ▶ **Connection** $\Rightarrow$ macroscopic variables emerge from microscopic interactions²

- ▶ 2 quantities *-only depending on time-* used to describe traffic systems
 - ⇒ **state** x_i (*position of vehicle i at time t*)
 - ⇒ **velocity** v_i (*speed of vehicle i at time t*)

- ▶ 2 quantities *-only depending on time-* used to describe traffic systems
 - ⇒ **state** x_i (*position of vehicle i at time t*)
 - ⇒ **velocity** v_i (*speed of vehicle i at time t*)
- ▶ Dynamics depend on **headway** ⇒ captures reaction effects explicitly

$$\dot{x}_i(t) = v(z_i(t)) \quad (3)$$

where $z_i(t)$ accounts for *surrounding* of vehicle i

- ▶ 3 quantities *-depending on space and time-* used to describe traffic systems
 - ⇒ relative density ρ (*number of vehicles per unit of length*)
 - ⇒ average velocity v (*mean speed of vehicles on a road segment*)
 - ⇒ flow rate f (*number of vehicles passing across a portion of the road during a period of time*)

- ▶ 3 quantities *-depending on space and time-* used to describe traffic systems
 - ⇒ relative density ρ (*number of vehicles per unit of length*)
 - ⇒ average velocity v (*mean speed of vehicles on a road segment*)
 - ⇒ flow rate f (*number of vehicles passing across a portion of the road during a period of time*)
- ▶ **Fundamental diagram** of traffic flow ⇒ $f(\rho) = \rho v_{\text{eq}}(\rho)$

- ▶ 3 quantities -*depending on space and time*- used to describe traffic systems
 - ⇒ **relative density** ρ (*number of vehicles per unit of length*)
 - ⇒ **average velocity** v (*mean speed of vehicles on a road segment*)
 - ⇒ **flow rate** f (*number of vehicles passing across a portion of the road during a period of time*)
- ▶ **Fundamental diagram** of traffic flow $\Rightarrow f(\rho) = \rho v_{\text{eq}}(\rho)$
- ▶ **Hydrodynamic equation** and **conservation law** lead to **LWR model**

$$\frac{\partial}{\partial t} \rho + \frac{\partial}{\partial x} (\rho v_{\text{eq}}(\rho)) = 0 \quad (4)$$

where $v_{\text{eq}}(\rho)$ is the **equilibrium** velocity

- ⇒ vehicles immediately adjust their velocity to *match equilibrium*: $v(t, x) = v_{\text{eq}}(\rho)$
- ⇒ *neglects acceleration* effects and assumes traffic flow behaves as a compressible fluid

Table of Contents

Introduction

Existing Traffic Flow Models

(Learning-Based) Optimization for Traffic Flow Reconstruction

Numerical experiments

Conclusion and Perspectives

- **Follow-the-Leader** (FtL), **microscopic** first order model
 - ⇒ dynamics of each vehicle depend on vehicle immediately in front

$$\begin{cases} \dot{x}_N^N(t) = v_{\max}, & t > 0, \\ \dot{x}_i^N(t) = v \left(\frac{L}{N(x_{i+1}^N(t) - x_i^N(t))} \right), & t > 0, \quad i = 0, \dots, N-1 \\ x_i^N(0) = \bar{x}_i^N, & i = 0, \dots, N \end{cases} \quad (5)$$

- ⇒ accurate traffic representation, **encodes individual movements**
- ⇒ computationally demanding, **requires more data**

- **Lighthill-William-Richards** (LWR), **macroscopic** traffic flow model
 - ⇒ vehicles treated as a continuous medium similar to particles in fluid
 - ⇒ one-dimensional (hyperbolic) conservation law

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t > 0, \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R} \end{cases} \quad (6)$$

- ⇒ faster implementation, **less data-intensive**
- ⇒ overlooks traffic heterogeneity, **oversimplifies traffic phenomena**

- ▶ **Convergence analysis of FtL approximation scheme towards LWR model³**

³holden`continuum`2017.

⁴francesco`rigorous`2015.

- ▶ **Convergence analysis of FtL approximation scheme towards LWR model**³
- ▶ **Link** between FtL and LWR based on atomization of initial density $\bar{\rho}$

$$\bar{x}_{i+1}^N := \sup \left\{ x \in \mathbb{R} : \int_{\bar{x}_i^N}^x \bar{\rho}(y) dy = \frac{L}{N} \right\}, \quad i = 0, \dots, N-1 \quad (7)$$


³holden`continuum`2017.

⁴francesco`rigorous`2015.

- ▶ **Convergence analysis of FtL approximation scheme towards LWR model**³
- ▶ **Link** between FtL and LWR based on atomization of initial density $\bar{\rho}$

$$\bar{x}_{i+1}^N := \sup \left\{ x \in \mathbb{R} : \int_{\bar{x}_i^N}^x \bar{\rho}(y) dy = \frac{L}{N} \right\}, \quad i = 0, \dots, N-1 \quad (7)$$

- ▶ Solution of PDE (5) can be recovered as **many particle limit**⁴ of ODE system (6)



Coupled Resolution of a Microscopic ODE System and a Macroscopic PDE

³holden`continuum`2017.

⁴francesco`rigorous`2015.

- Hybrid micro-macro models explored in traffic density reconstruction⁵

$$\begin{cases} \dot{x}_N^N(t) = v_{\max}, & t > 0, \\ \dot{x}_i^N(t) = v(\rho(t, x_i^N(t))), & t > 0, \quad i = 0, \dots, N-1 \\ \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = \gamma^2 \frac{\partial^2}{\partial x^2} \rho(t, x), & x \in \mathbb{R}, \quad t > 0, \end{cases} \quad (8)$$

where $\gamma^2 \frac{\partial^2}{\partial x^2}$ is a diffusion correction term to handle discontinuous solutions of original PDE

⁵barreau`physics-informed`2021.

⁶liu`learning-based`2020.

- **Hybrid micro-macro models** explored in traffic density reconstruction⁵

$$\begin{cases} \dot{x}_N^N(t) = v_{\max}, & t > 0, \\ \dot{x}_i^N(t) = v(\rho(t, x_i^N(t))), & t > 0, \quad i = 0, \dots, N-1 \\ \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = \gamma^2 \frac{\partial^2}{\partial x^2} \rho(t, x), & x \in \mathbb{R}, \quad t > 0, \end{cases} \quad (8)$$

where $\gamma^2 \frac{\partial^2}{\partial x^2}$ is a diffusion correction term to handle discontinuous solutions of original PDE

- **Partial state reconstruction**⁶ using measurements from probe vehicles (PVs)
 - ⇒ low penetration rate $N_{\text{probes}} \ll N_{\text{total}}$
 - ⇒ recover density ρ from **limited** trajectories

⁵barreau'physics-informed'2021.

⁶liu'learning-based'2020.

- **Hybrid micro-macro models** explored in traffic density reconstruction⁵

$$\begin{cases} \dot{x}_N^N(t) = v_{\max}, & t > 0, \\ \dot{x}_i^N(t) = v(\rho(t, x_i^N(t))), & t > 0, \quad i = 0, \dots, N-1 \\ \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = \gamma^2 \frac{\partial^2}{\partial x^2} \rho(t, x), & x \in \mathbb{R}, \quad t > 0, \end{cases} \quad (8)$$

where $\gamma^2 \frac{\partial^2}{\partial x^2}$ is a diffusion correction term to handle discontinuous solutions of original PDE

- **Partial state reconstruction**⁶ using measurements from probe vehicles (PVs)
 - ⇒ low penetration rate $N_{\text{probes}} \ll N_{\text{total}}$
 - ⇒ recover density ρ from **limited** trajectories
- **Requires access to real-time positions, densities and instantaneous speeds** of PVs

⁵barreau'physics-informed'2021.

⁶liu'learning-based'2020.

- ▶ **Prior approaches rely on knowledge of initial density $\bar{\rho}$**
⇒ **No access** to this critical information, need to **leverage available data**

⁵barreau`physics-informed`2021.

⁶liu`learning-based`2020.

Table of Contents

Introduction

Existing Traffic Flow Models

(Learning-Based) Optimization for Traffic Flow Reconstruction

Numerical experiments

Conclusion and Perspectives

- ▶ **Limited data scenario** $\Rightarrow$ only **initial and final** $\{(\bar{x}_i^N, \bar{y}_i^N)\}_{i=0}^n$ positions of **PVs**

Parametrized Microscopic Model

- ▶ **Limited data scenario** $\Rightarrow$ only **initial and final** $\{(\bar{x}_i^N, \bar{y}_i^N)\}_{i=0}^n$ positions of **PVs**
- ▶ **Enhanced** version of FtL scheme (5) adding a parameter
 - $\Rightarrow \alpha^N$ **accounts for unobserved vehicles** between consecutive PVs
 - $\Rightarrow$ bridges **discrete** (vehicle-level) dynamics **to continuous** (density-level) dynamics

- ▶ **Limited data scenario** $\Rightarrow$ only **initial and final** $\{(\bar{x}_i^N, \bar{y}_i^N)\}_{i=0}^n$ positions of **PVs**
- ▶ **Enhanced** version of FtL scheme (5) adding a parameter
 - $\Rightarrow \alpha^N$ **accounts for unobserved vehicles** between consecutive PVs
 - $\Rightarrow$ bridges **discrete** (vehicle-level) dynamics **to continuous** (density-level) dynamics
- ▶ Parametrized ODE system with **finite time horizon**

$$\begin{cases} \dot{x}_n^N(t) = v_{\max}, & t \in (0, T] \\ \dot{x}_i^N(t) = v(\rho_i^N(t)), & t \in (0, T] \quad i = 0, \dots, n-1 \\ x_i^N(0) = \bar{x}_i^N, & i = 0, \dots, n \end{cases} \quad (9)$$

$\Rightarrow$ local discrete densities

$$\rho_i^N(t) := \frac{\alpha_i^N L}{N(x_{i+1}^N(t) - x_i^N(t))}, \quad t \in (0, T], \quad i = 0, \dots, n-1 \quad (10)$$

- ▶ **Limited data scenario** $\Rightarrow$ only **initial and final** $\{(\bar{x}_i^N, \bar{y}_i^N)\}_{i=0}^n$ positions of **PVs**
- ▶ **Enhanced** version of FtL scheme (5) adding a parameter
 $\Rightarrow \alpha^N$ **accounts for unobserved vehicles** between consecutive PVs
 $\Rightarrow$ bridges **discrete** (vehicle-level) dynamics **to continuous** (density-level) dynamics
- ▶ Parametrized ODE system with **finite time horizon**

$$\begin{cases} \dot{x}_n^N(t) = v_{\max}, & t \in (0, T] \\ \dot{x}_i^N(t) = v(\rho_i^N(t)), & t \in (0, T] \quad i = 0, \dots, n-1 \\ x_i^N(0) = \bar{x}_i^N, & i = 0, \dots, n \end{cases} \quad (9)$$

$\Rightarrow$ local discrete densities

$$\rho_i^N(t) := \frac{\alpha_i^N L}{N (x_{i+1}^N(t) - x_i^N(t))}, \quad t \in (0, T], \quad i = 0, \dots, n-1 \quad (10)$$

- ▶ **Piecewise constant** Eulerian discrete density

$$\rho^N(t, x) := \sum_{i=0}^{N-1} \rho_i^N(t) \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T] \quad (11)$$

► Assumptions on velocity

$$v \in C^1([0, +\infty)) \quad (12a)$$

$$v \text{ is decreasing on } [0, +\infty) \quad (12b)$$

$$v(0) = v_{\max} < \infty \quad (12c)$$

► Assumptions on velocity

$$v \in C^1([0, +\infty)) \quad (12a)$$

$$v \text{ is decreasing on } [0, +\infty) \quad (12b)$$

$$v(0) = v_{\max} < \infty \quad (12c)$$

► Local existence and uniqueness of solution to (9) (for fixed α) via Picard-Lindelöf

► Assumptions on velocity

$$v \in C^1([0, +\infty)) \quad (12a)$$

$$v \text{ is decreasing on } [0, +\infty) \quad (12b)$$

$$v(0) = v_{\max} < \infty \quad (12c)$$

► Local existence and uniqueness of solution to (9) (for fixed α) via Picard-Lindelöf

► Condition on initial car positions $\bar{x}_0^N < \bar{x}_1^N < \dots < \bar{x}_{n-1}^N < \bar{x}_n^N$
 $\Rightarrow$ global existence

Lemma (Discrete maximum principle)

For solution $x(t)$ of (9) with v satisfying (12a)-(12c), for all $i = 0, \dots, n-1$,

$$\frac{\alpha_i^N L}{NM} \leq x_{i+1}^N(t) - x_i^N(t) \leq \bar{x}_n^N - \bar{x}_0^N + (v_{\max} - v(M)) t, \quad \forall t \in [0, T], \quad (13)$$

where $M := \max_i \left(\frac{\alpha_i^N L}{N(\bar{x}_{i+1}^N - \bar{x}_i^N)} \right)$

- Physical conditions on $\alpha := \alpha^N$ induce **feasible set**

$$\mathcal{A}^N := \left\{ \alpha \in \mathbb{R}^n : \quad \alpha_i \in [1, \bar{z}_i^N], \quad i = 0, \dots, n-1, \quad \sum_{i=0}^{n-1} \alpha_i = N \right\} \quad (14)$$

$$\text{with } \bar{z}_i^N := \min \left\{ \frac{N(\bar{x}_{i+1}^N - \bar{x}_i^N)}{L}, \frac{N(\bar{y}_{i+1}^N - \bar{y}_i^N)}{L} \right\}, \quad i = 0, \dots, n-1$$

- Physical conditions on $\alpha := \alpha^N$ induce **feasible set**

$$\mathcal{A}^N := \left\{ \alpha \in \mathbb{R}^n : \quad \alpha_i \in [1, \bar{z}_i^N], \quad i = 0, \dots, n-1, \quad \sum_{i=0}^{n-1} \alpha_i = N \right\} \quad (14)$$

$$\text{with } \bar{z}_i^N := \min \left\{ \frac{N(\bar{x}_{i+1}^N - \bar{x}_i^N)}{L}, \frac{N(\bar{y}_{i+1}^N - \bar{y}_i^N)}{L} \right\}, \quad i = 0, \dots, n-1$$

- **Approximate density reconstruction**⁷ $\Rightarrow$ find **optimal** interaction parameter α

$$\begin{aligned} & \underset{\alpha}{\text{minimize}} \quad \frac{1}{2} \|x(T) - \bar{y}\|^2 \\ & \text{s.t.} \quad \dot{x}(t) = V(W_\alpha x(t) + b_\alpha(t)) \\ & \quad x(0) = \bar{x} \\ & \quad \alpha \in \mathcal{A}^N \end{aligned} \quad (15)$$

⁷baloul'reconstruction'2025.

- Physical conditions on $\alpha := \alpha^N$ induce **feasible set**

$$\mathcal{A}^N := \left\{ \alpha \in \mathbb{R}^n : \quad \alpha_i \in [1, \bar{z}_i^N], \quad i = 0, \dots, n-1, \quad \sum_{i=0}^{n-1} \alpha_i = N \right\} \quad (14)$$

$$\text{with } \bar{z}_i^N := \min \left\{ \frac{N(\bar{x}_{i+1}^N - \bar{x}_i^N)}{L}, \frac{N(\bar{y}_{i+1}^N - \bar{y}_i^N)}{L} \right\}, \quad i = 0, \dots, n-1$$

- **Approximate density reconstruction**⁷ $\Rightarrow$ find **optimal** interaction parameter α

$$\begin{aligned} & \underset{\alpha}{\text{minimize}} \quad \frac{1}{2} \|x(T) - \bar{y}\|^2 \\ & \text{s.t.} \quad \dot{x}(t) = V(W_\alpha x(t) + b_\alpha(t)) \\ & \quad x(0) = \bar{x} \\ & \quad \alpha \in \mathcal{A}^N \end{aligned} \quad (15)$$

- **Existence of solutions** guaranteed by continuity of $V := v \circ \frac{1}{\cdot}$ and compactness of $\mathcal{A}^N$

- Physical conditions on $\alpha := \alpha^N$ induce **feasible set**

$$\mathcal{A}^N := \left\{ \alpha \in \mathbb{R}^n : \quad \alpha_i \in [1, \bar{z}_i^N], \quad i = 0, \dots, n-1, \quad \sum_{i=0}^{n-1} \alpha_i = N \right\} \quad (14)$$

$$\text{with } \bar{z}_i^N := \min \left\{ \frac{N(\bar{x}_{i+1}^N - \bar{x}_i^N)}{L}, \frac{N(\bar{y}_{i+1}^N - \bar{y}_i^N)}{L} \right\}, \quad i = 0, \dots, n-1$$

- **Approximate density reconstruction**⁷ $\Rightarrow$ find **optimal** interaction parameter α

$$\begin{aligned} & \underset{\alpha}{\text{minimize}} \quad \frac{1}{2} \|x(T) - \bar{y}\|^2 \\ & \text{s.t.} \quad \dot{x}(t) = V(W_\alpha x(t) + b_\alpha(t)) \\ & \quad x(0) = \bar{x} \\ & \quad \alpha \in \mathcal{A}^N \end{aligned} \quad (15)$$

- **Existence of solutions** guaranteed by continuity of $V := v \circ \frac{1}{\cdot}$ and compactness of $\mathcal{A}^N$
- No uniqueness (a priori) since **nonlinear dynamics can lead to multiple minima**

- ▶ Dataset consists of **artificial data** based on simulated (classical) FtL dynamics (5)
- ▶ Sampling of PVs yielding a **balanced representation** of overall traffic

- ▶ Dataset consists of **artificial data** based on simulated (classical) FtL dynamics (5)
- ▶ Sampling of PVs yielding a **balanced representation** of overall traffic
- ▶ **Neural network** architecture designed to **understand dynamics of traffic**

- ▶ Dataset consists of **artificial data** based on simulated (classical) FtL dynamics (5)
- ▶ Sampling of PVs yielding a **balanced representation** of overall traffic
- ▶ **Neural network** architecture designed to **understand dynamics of traffic**
- ▶ Residual network (ResNet) where **each block corresponds to a single time step**
- ▶ Input $\bar{x}$ and state $x(\cdot)$ is **propagated by mirroring Euler discretization**

$$x(t + \Delta t) = x(t) + V(Wx(t) + b)\Delta t \quad (16)$$

- ▶ Weights and biases W, b are functions of α


$$\begin{cases} W_{i,i} := -\frac{N}{\alpha_i L}, & i = 0, \dots, n-1, \\ W_{i,i+1} := \frac{N}{\alpha_i L}, & i = 1, \dots, n-2, \\ W_{i,j} := 0, & \text{otherwise,} \end{cases} \quad b_i(t) := \delta_{i,n} \frac{N}{\alpha_i L} \left(v_{\max} t + \bar{x}_n^N \right), \quad t \in [0, T] \quad (17)$$

- ▶ Nonlinear dynamic map V acts as physics grounded activation function

- ▶ **Backpropagation to minimize predictions errors** $\mathcal{L}^{\text{train}}(x(T), \bar{y}) = \frac{1}{n} \sum_{j=0}^n |x_j^\alpha(T) - \bar{y}_j^N|^2$

Neural Network for Constrained Optimization

Learning Architecture



- ▶ Through predicted parameter $\bar{\alpha}$, training yields piecewise constant discrete density

$$\rho^N(t, x) = \sum_{i=0}^{n-1} \frac{\bar{\alpha}_i L}{N(x_{i+1}^N(t) - x_i^N(t))} \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T], \quad (18)$$

- ▶ Through predicted parameter $\bar{\alpha}$, training yields piecewise constant discrete density

$$\rho^N(t, x) = \sum_{i=0}^{n-1} \frac{\bar{\alpha}_i L}{N(x_{i+1}^N(t) - x_i^N(t))} \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T], \quad (18)$$

- ▶ Simulation on **test data** by solving ODE system

$$\begin{cases} \dot{x}_i^N(t) = v(\rho^N(t, x_i(t)^+)) , & t \in (0, T], \\ x_i^N(0) = \bar{x}_i^N & i = 0, \dots, n_{\text{test}} \end{cases} \quad (19)$$

- ▶ Through predicted parameter $\bar{\alpha}$, training yields piecewise constant discrete density

$$\rho^N(t, x) = \sum_{i=0}^{n-1} \frac{\bar{\alpha}_i L}{N(x_{i+1}^N(t) - x_i^N(t))} \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T], \quad (18)$$

- ▶ Simulation on **test data** by solving ODE system

$$\begin{cases} \dot{x}_i^N(t) = v(\rho^N(t, x_i(t)^+)), & t \in (0, T], \\ x_i^N(0) = \bar{x}_i^N & i = 0, \dots, n_{\text{test}} \end{cases} \quad (19)$$

- ▶ Assess model's performance by measuring test error $L^{\text{test}}(x(T), \bar{y}) = \frac{1}{n_{\text{test}}} \sum_{j=0}^{n_{\text{test}}} |x_j^{\bar{\alpha}}(T) - \bar{y}_i^N|^2$

Theorem Convergence of approximate density to solution of LWR

Under some assumptions, piecewise-constant density

$$\rho^N(t, x) = \sum_{i=0}^{n-1} \frac{\bar{\alpha}_i^N L}{N(x_{i+1}^N(t) - x_i^N(t))} \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T], \quad (21)$$

where $\bar{\alpha}_i^N \in \mathcal{A}^N$ is a solution to (15) converges to **unique entropy** solution ρ of

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t \in [0, T], \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R} \end{cases} \quad (22)$$

Convergence Result

- Weak solution of (6) is **entropy admissible** if it satisfies **Kruzhkov entropy condition**

$$\int_0^T \int_{\mathbb{R}} |u - k| \frac{\partial \phi}{\partial t} + \text{sign}(u - k)(f(u) - f(k)) \frac{\partial \phi}{\partial x} dx dt \geq 0, \quad \forall k \in \mathbb{R} \quad (20)$$

Theorem Convergence of approximate density to solution of LWR

Under some assumptions, piecewise-constant density


$$\rho^N(t, x) = \sum_{i=0}^{n-1} \frac{\bar{\alpha}_i^N L}{N(x_{i+1}^N(t) - x_i^N(t))} \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T], \quad (21)$$

where $\bar{\alpha}_i^N \in \mathcal{A}^N$ is a solution to (15) converges to **unique entropy** solution ρ of

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t \in [0, T], \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R} \end{cases} \quad (22)$$

- Impose a condition that ensures **controlled growth of α^N**

Scheme of Model



Traffic Flow Reconstruction Pipeline

Table of Contents

Introduction

Existing Traffic Flow Models

(Learning-Based) Optimization for Traffic Flow Reconstruction


Numerical experiments

Conclusion and Perspectives

- ▶ Parameters
 - ▶ Maximum traffic speed $v_{\max} = 120$ km/h
 - ▶ Maximum traffic density $\rho_{\max} = 200$ cars/km
 - ▶ Greenshields velocity $v(\rho) = v_{\max} \max \left\{ 1 - \frac{\rho}{\rho_{\max}}, 0 \right\}$, $\rho \in [0, \rho_{\max}]$
 - ▶ Final time horizon $T = 0.1$ h or $T = 0.2$
- ▶ Sampling such **10% of total fleet serve as PVs for training and 2.5% for testing**

- ▶ Parameters
 - ▶ Maximum traffic speed $v_{\max} = 120$ km/h
 - ▶ Maximum traffic density $\rho_{\max} = 200$ cars/km
 - ▶ Greenshields velocity $v(\rho) = v_{\max} \max \left\{ 1 - \frac{\rho}{\rho_{\max}}, 0 \right\}$, $\rho \in [0, \rho_{\max}]$
 - ▶ Final time horizon $T = 0.1$ h or $T = 0.2$
- ▶ Sampling such **10% of total fleet serve as PVs for training and 2.5% for testing**
- ▶ Three traffic scenarii modelled
 1. **Rarefaction wave** represents a **smooth transition** in traffic conditions
 2. **Shock wave** represents an **abrupt transition** in traffic conditions
 3. **Stop-and-go wave** characterized by **alternating regions of congestion and free flow**





Rarefaction wave scenario



(a) $N = 1000$

Comparison of **predicted** and **target** final PV positions: **Top** Results from **training** procedure, **Bottom** Results on **test** sounds


Rarefaction wave scenario



(a) $N = 1000$





(b) $N = 3000$

Comparison of **predicted** and **target** final PV positions: **Top** Results from **training** procedure, **Bottom** Results on **test** sounds



(a) $N = 1000$



Comparison of **reconstructed** and **macroscopic** densities: **Top** Initial densities, **Bottom** Final densities



(a) $N = 1000$



(b) $N = 3000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Initial densities, **Bottom** Final densities



(a) $N = 1000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Reconstructed density, **Bottom** Godunov LWR density




(a) $N = 1000$

(b) $N = 3000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Reconstructed density, **Bottom** Godunov LWR density



Shock wave scenario





(a) $N = 1000$

Comparison of **predicted** and **target** final PV positions: **Top** Results from **training** procedure, **Bottom** Results on **test** sounds

Shock wave scenario





(a) $N = 1000$







(b) $N = 3000$

Comparison of **predicted** and **target** final PV positions: **Top** Results from **training** procedure, **Bottom** Results on **test** sounds



(a) $N = 1000$



Comparison of **reconstructed** and **macroscopic** densities: **Top** Initial densities, **Bottom** Final densities



(a) $N = 1000$





(b) $N = 3000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Initial densities, **Bottom** Final densities



(a) $N = 1000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Reconstructed density, **Bottom** Godunov LWR density




(a) $N = 1000$

(b) $N = 3000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Reconstructed density, **Bottom** Godunov LWR density





Stop-and-go wave scenario



(a) $N = 1000$

Comparison of **predicted** and **target** final PV positions: **Top** Results from **training** procedure, **Bottom** Results on **test** sounds


Stop-and-go wave scenario



(a) $N = 1000$





(b) $N = 3000$

Comparison of **predicted** and **target** final PV positions: **Top** Results from **training** procedure, **Bottom** Results on **test** sounds



(a) $N = 1000$



Comparison of **reconstructed** and **macroscopic** densities: **Top** Initial densities, **Bottom** Final densities



(a) $N = 1000$



(b) $N = 3000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Initial densities, **Bottom** Final densities



(a) $N = 1000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Reconstructed density, **Bottom** Godunov LWR density



(a) $N = 1000$

(b) $N = 3000$

Comparison of **reconstructed** and **macroscopic** densities: **Top** Reconstructed density, **Bottom** Godunov LWR density

Table of Contents

Introduction

Existing Traffic Flow Models

(Learning-Based) Optimization for Traffic Flow Reconstruction

Numerical experiments

Conclusion and Perspectives

Traffic State Reconstruction Approaches

- ▶ Model-Based Method
 - ⇒ uses microscopic and macroscopic models
 - ⇒ provides **theoretical guarantees**
 - ⇒ struggles to capture **real-world complexities**

Traffic State Reconstruction Approaches

- ▶ Model-Based Method
 - ⇒ uses microscopic and macroscopic models
 - ⇒ provides **theoretical guarantees**
 - ⇒ struggles to capture **real-world complexities**
- ▶ Data-Driven Method
 - ⇒ **learns patterns** directly from measurement data
 - ⇒ derives system properties or **predicts near-future states**
 - ⇒ requires **extensive data** for effectiveness

Traffic State Reconstruction Approaches

- ▶ Model-Based Method
 - ⇒ uses microscopic and macroscopic models
 - ⇒ provides **theoretical guarantees**
 - ⇒ struggles to capture **real-world complexities**
- ▶ Data-Driven Method
 - ⇒ **learns patterns** directly from measurement data
 - ⇒ derives system properties or **predicts near-future states**
 - ⇒ requires **extensive data** for effectiveness
- ▶ Our Approach
 - ⇒ combines models and data to **address sparsity and improve realism**
 - ⇒ **Integrates physical priors with data observations**
 - ⇒ achieves **reliable traffic reconstruction with limited observations**

- Conservation law with **unilateral constraint**⁸ (toll gate)

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t > 0, \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R}, \\ f(\rho(t, 0)) \leq q(t), & t > 0. \end{cases} \quad (23)$$

⁸colombo`well`2007.

⁹liard`entropic`2020.

- Conservation law with **unilateral constraint**⁸ (toll gate)

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t > 0, \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R}, \\ f(\rho(t, 0)) \leq q(t), & t > 0. \end{cases} \quad (23)$$

- Conservation law with **moving bottleneck**⁹ (slow vehicle)

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t > 0, \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R}, \\ f(\rho(t, y(t))) - \dot{y}(t)\rho(t, y(t)) \leq \frac{\alpha \rho_{\max}}{4v_{\max}} (v_{\max} - \dot{y}(t))^2, & t > 0, \\ \dot{y}(t) = \omega(\rho(t, y(t)_+)), & t > 0, \\ y(0) = y_0 & \end{cases} \quad (24)$$

⁸colombo`well`2007.

⁹liard`entropic`2020.

- Network¹⁰ with a junction¹¹ J and N incoming roads and M outgoing ones

$$\begin{cases} \frac{\partial}{\partial t} \rho_l(t, x) + \frac{\partial}{\partial x} (f(\rho_l(t, x))) = 0, & t > 0, \quad x \in I_l, \quad l = 1, \dots, N + M \\ \rho_l(0, x) = \rho_{0,l}(x), & x \in I_l = [a_l, b_l], \quad l = 1, \dots, N + M \end{cases} \quad (25)$$

$$\Rightarrow \sum_{i=1}^N f(\rho_i(t, (b_i)_-)) = \sum_{j=N+1}^{N+M} f(\rho_j(t, (a_j)_+)) \quad (\text{Rankine Hugoniot})$$

$$\Rightarrow \sum_{i=1}^N f(\rho_i(t, (b_i)_-)) \text{ is maximized}^{12} \text{ s.t. } f(\rho_j(\cdot, (a_j)_+)) = \sum_{i=1}^N a_{j,i} f(\rho_i(\cdot, (b_i)_-))$$

¹⁰monneau`structure`2024.

¹¹coclite`traffic`2005.

¹²garavello2006traffic.

Lemma (Discrete maximum principle)

For solution $x(t)$ of (9) with v satisfying (12a)-(12c), for all $i = 0, \dots, n-1$,

$$\frac{\alpha_i^N L}{NM} \leq x_{i+1}^N(t) - x_i^N(t) \leq \bar{x}_n^N - \bar{x}_0^N + (v_{\max} - v(M)) t, \quad \forall t \in [0, T], \quad (26)$$

where $M := \max_i \left(\frac{\alpha_i^N L}{N(\bar{x}_{i+1}^N - \bar{x}_i^N)} \right)$

Sketch of proof

- ▶ Lower bound is satisfied at $t = 0$, aim at extending property for all times up to T

Sketch of proof

- ▶ Lower bound is satisfied at $t = 0$, aim at **extending property for all times up to T**
- ▶ Equivalent to show

$$\inf_{0 < t \leq T} [x_{i+1}(t) - x_i(t)] \geq \frac{\alpha_i^N L}{NM}, \quad i = 0, \dots, n-1. \quad (27)$$

⇒ **recursive argument** (backward from $n-1$ to 0)

- ▶ Lower bound is satisfied at $t = 0$, aim at **extending property for all times up to T**
- ▶ Equivalent to show

$$\inf_{0 < t \leq T} [x_{i+1}(t) - x_i(t)] \geq \frac{\alpha_i^N L}{NM}, \quad i = 0, \dots, n-1. \quad (27)$$

⇒ **recursive argument** (backward from $n-1$ to 0)

- ▶ Property is true for $i = n-1$

$$\begin{aligned} x_n(t) - x_{n-1}(t) &= \bar{x}_n - \bar{x}_{n-1} + \int_0^t \left(v_{\max} - v \left(\frac{\alpha_n^N L}{N(x_n(s) - x_{n-1}(s))} \right) \right) ds \\ &\geq \bar{x}_n - \bar{x}_{n-1} \geq \frac{\alpha_{n-1}^N L}{NM}. \end{aligned}$$

- ▶ Lower bound is satisfied at $t = 0$, aim at **extending property for all times up to T**
- ▶ Equivalent to show

$$\inf_{0 < t \leq T} [x_{i+1}(t) - x_i(t)] \geq \frac{\alpha_i^N L}{NM}, \quad i = 0, \dots, n-1. \quad (27)$$

⇒ **recursive argument** (backward from $n-1$ to 0)

- ▶ Property is true for $i = n-1$

$$\begin{aligned} x_n(t) - x_{n-1}(t) &= \bar{x}_n - \bar{x}_{n-1} + \int_0^t \left(v_{\max} - v \left(\frac{\alpha_n^N L}{N(x_n(s) - x_{n-1}(s))} \right) \right) ds \\ &\geq \bar{x}_n - \bar{x}_{n-1} \geq \frac{\alpha_{n-1}^N L}{NM}. \end{aligned}$$

- ▶ Assume property is verified for $j+1$ and prove it is still satisfied for j

$$\inf_{0 < t \leq T} [x_{j+2}(t) - x_{j+1}(t)] \geq \frac{\alpha_{j+1}^N L}{NM}. \quad (28)$$

Sketch of proof

- By contradiction, assume that there exists $0 \leq t_1 < t_2$ such that

$$\left\{ \begin{array}{ll} x_{j+1}(t) - x_j(t) \geq \frac{\alpha_j^N L}{NM}, & t < t_1 \\ x_{j+1}(t) - x_j(t) = \frac{\alpha_j^N L}{NM}, & t = t_1 \\ x_{j+1}(t) - x_j(t) < \frac{\alpha_j^N L}{NM}, & t_1 < t \leq t_2. \end{array} \right. \quad (29)$$

Sketch of proof

- By contradiction, assume that there exists $0 \leq t_1 < t_2$ such that

$$\left\{ \begin{array}{ll} x_{j+1}(t) - x_j(t) \geq \frac{\alpha_j^N L}{NM}, & t < t_1 \\ x_{j+1}(t) - x_j(t) = \frac{\alpha_j^N L}{NM}, & t = t_1 \\ x_{j+1}(t) - x_j(t) < \frac{\alpha_j^N L}{NM}, & t_1 < t \leq t_2. \end{array} \right. \quad (29)$$

- Since v is decreasing

$$\begin{aligned} x_j(t) &= x_j(t_1) + \int_{t_1}^t v \left(\frac{\alpha_j^N L}{N(x_{j+1}(s) - x_j(s))} \right) ds \\ &\leq x_j(t_1) + v(M)(t - t_1), \end{aligned}$$

- Moreover from (28), for $t_1 < t \leq t_2$,

$$x_{j+1}(t) = x_{j+1}(t_1) + \int_{t_1}^t v \left(\frac{\alpha_{j+1}^N L}{N(x_{j+2}(s) - x_{j+1}(s))} \right) ds \geq x_{j+1}(t_1) + v(M)(t - t_1)$$

$$\Rightarrow x_{j+1}(t) - x_j(t) \geq x_{j+1}(t_1) - x_j(t_1) = \frac{\alpha_j^N L}{NM}$$

which contradicts (29), so that (27) is satisfied

- Show upper bound for $i = 0, \dots, n-1$ and $t \in [0, T]$
- Recalling assumptions on v and applying system's dynamics

$$\begin{aligned}x_{i+1}(t) - x_i(t) &= x_{i+1}(0) - x_i(0) + \int_0^t (\dot{x}_{i+1}(s) - \dot{x}_i(s)) ds \\&\leq \bar{x}_{i+1} - \bar{x}_i + \int_0^t \left(v_{\max} - v \left(\frac{\alpha_i^N L}{N(x_{i+1}(s) - x_i(s))} \right) \right) ds \\&\leq \bar{x}_n - \bar{x}_0 + (v_{\max} - v(M)) t,\end{aligned}$$

- Last equality is obtained from lower bound $\Rightarrow$ proof is complete

Outline of Convergence Analysis

- ▶ Prove that ρ^N predicted by ML converges to solution of LWR (6) when the $N \rightarrow \infty$

Outline of Convergence Analysis

- ▶ Prove that ρ^N predicted by ML converges to solution of LWR (6) when the $N \rightarrow \infty$
- ▶ Main challenge is imposing a condition on distribution of α which would guarantee convergence

Outline of Convergence Analysis

- ▶ Prove that ρ^N predicted by ML converges to solution of LWR (6) when the $N \rightarrow \infty$
- ▶ Main challenge is imposing a condition on distribution of α which would guarantee convergence
- ▶ Demonstrate that $\rho^N(0, \cdot)$ converges to $\bar{\rho}$ in LWR (6)

Outline of Convergence Analysis

- ▶ Prove that ρ^N **predicted by ML** converges to solution of LWR (6) when the $N \rightarrow \infty$
- ▶ Main challenge is imposing a **condition on distribution of α** which would guarantee convergence
- ▶ Demonstrate that $\rho^N(0, \cdot)$ converges to $\bar{\rho}$ in LWR (6)
- ▶ Consider empirical discrete density

$$\hat{\rho}^N(t, \cdot) := \frac{L}{N} \sum_{i=0}^{n-1} \alpha_i^N \delta_{x_i(t)}(\cdot), \quad t \in [0, T]. \quad (30)$$

- ▶ Prove that ρ^N **predicted by ML** converges to solution of LWR (6) when the $N \rightarrow \infty$
- ▶ Main challenge is imposing a **condition on distribution of α** which would guarantee convergence
- ▶ Demonstrate that $\rho^N(0, \cdot)$ converges to $\bar{\rho}$ in LWR (6)
- ▶ Consider empirical discrete density

$$\hat{\rho}^N(t, \cdot) := \frac{L}{N} \sum_{i=0}^{n-1} \alpha_i^N \delta_{x_i(t)}(\cdot), \quad t \in [0, T]. \quad (30)$$

- ▶ **Important observation:** by construction, initial traffic density must satisfy

$$\bar{x}_{i+1} = \sup \left\{ x \in \mathbb{R} : \int_{\bar{x}_i}^x \bar{\rho}(y) dy \leq \frac{\alpha_i L}{N} \right\}, \quad i = 0, \dots, n-1 \quad (31)$$

$\Rightarrow$ although no access to ground-truth initial car density $\bar{\rho}$, initial positions $\bar{x}_i$ verify (31)

Theorem Convergence of approximate density to solution of LWR

Under some assumptions, piecewise-constant density

$$\rho^N(t, x) = \sum_{i=0}^{n-1} \frac{\bar{\alpha}_i^N L}{N(x_{i+1}^N(t) - x_i^N(t))} \chi_{[x_i^N(t), x_{i+1}^N(t))}(x), \quad x \in \mathbb{R}, \quad t \in [0, T], \quad (32)$$

where $\bar{\alpha}_i^N \in \mathcal{A}^N$ is a solution to (15) converges to **unique entropy** solution ρ of

$$\begin{cases} \frac{\partial}{\partial t} \rho(t, x) + \frac{\partial}{\partial x} f(\rho(t, x)) = 0, & x \in \mathbb{R}, \quad t \in [0, T], \\ \rho(0, x) = \bar{\rho}(x), & x \in \mathbb{R} \end{cases} \quad (33)$$

Sketch of proof

- ▶ Ensures discretization aligns consistently with true initial density when $N \rightarrow \infty$
- ▶ Notations: for $t \in [0, T]$, $\rho(t) := \rho(t, \cdot)$ and $\hat{\rho}(t) := \hat{\rho}(t, \cdot)$
In particular, at $t = 0$, $\rho(0) := \rho(0, \cdot)$ and $\hat{\rho}(0) := \hat{\rho}(0, \cdot)$

- ▶ Ensures discretization aligns consistently with true initial density when $N \rightarrow \infty$
- ▶ Notations: for $t \in [0, T]$, $\rho(t) := \rho(t, \cdot)$ and $\hat{\rho}(t) := \hat{\rho}(t, \cdot)$
In particular, at $t = 0$, $\rho(0) := \rho(0, \cdot)$ and $\hat{\rho}(0) := \hat{\rho}(0, \cdot)$
- ▶ Use **Wasserstein distance** defined in **francesco rigorous 2015** by

$$W_{L,1}(f, g) = \|f([\cdot - \infty, \cdot]) - g([\cdot - \infty, \cdot])\|_{L^1(\mathbb{R}, \mathbb{R})} \quad (34)$$

Proposition

Let $\bar{\rho}$ satisfy (31) and assume that

$$\max_{i=0, \dots, n-1} \alpha_i^N = o(N) \quad (35)$$

Then $(\rho^N(0))_{n \in \mathbb{N}}$ and $(\hat{\rho}^N(0))_{n \in \mathbb{N}}$ converge to $\bar{\rho}$ in the sense of the $W_{L,1}$ -Wasserstein distance in (34)

Remark

A particular case of assumption (35) is when $\max_{i=0, \dots, n-1} \alpha_i^N \leq \frac{CN}{\log(N)}$ for some $C > 0$

- Using $l_N := L/N$, $W_{L,1}$ - distance and discrete density in (10)

$$\begin{aligned} W_{L,1}(\rho^N(0), \hat{\rho}^N(0)) &= \sum_{i=0}^{n-1} \int_{\bar{x}_i}^{\bar{x}_{i+1}^N} \left(\alpha_i^N l_N - \rho_i^N(t) (x - \bar{x}_i) \right) dx \\ &= \sum_{i=0}^{n-1} \alpha_i^N l_N \int_{\bar{x}_i}^{\bar{x}_{i+1}^N} \left(1 - \frac{x - \bar{x}_i}{\bar{x}_{i+1} - \bar{x}_i} \right) dx \\ &\leq \max_{i=0, \dots, n} \{ \alpha_i^N \} l_N (\bar{x}_n - \bar{x}_0) \end{aligned} \tag{36}$$

⇒ it suffices to prove that $(\hat{\rho}^N(0))_{n \in \mathbb{N}}$ converges to $\bar{\rho}$ in sense of $W_{L,1}$ - distance

Sketch of proof

- Using $l_N := L/N$, $W_{L,1}$ - distance and discrete density in (10)

$$\begin{aligned} W_{L,1}(\rho^N(0), \hat{\rho}^N(0)) &= \sum_{i=0}^{n-1} \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(\alpha_i^N l_N - \rho_i^N(t) (x - \bar{x}_i) \right) dx \\ &= \sum_{i=0}^{n-1} \alpha_i^N l_N \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(1 - \frac{x - \bar{x}_i}{\bar{x}_{i+1} - \bar{x}_i} \right) dx \\ &\leq \max_{i=0, \dots, n} \{ \alpha_i^N \} l_N (\bar{x}_n - \bar{x}_0) \end{aligned} \tag{36}$$

⇒ it suffices to prove that $(\hat{\rho}^N(0))_{n \in \mathbb{N}}$ converges to $\bar{\rho}$ in sense of $W_{L,1}$ - distance

- Using expressions of both Euler (11) and empirical (30) discrete densities

$$\begin{aligned} &W_{L,1}(\hat{\rho}^N(0), \bar{\rho}) \\ &= \sum_{i=0}^{n-2} \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(\left(\sum_{j=0}^{i-1} \alpha_j^N l_N - \int_{\bar{x}_0}^{\bar{x}_i} \bar{\rho}(y) dy \right) + \left(\alpha_i^N l_N - \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) \right) dx \\ &\quad + \int_{\bar{x}_{n-1}}^{\bar{x}_n} \left(\sum_{j=0}^{n-2} \alpha_j^N l_N - \int_{\bar{x}_0}^{\bar{x}_{n-1}} \bar{\rho}(y) dy \right) + \left(\alpha_{n-1}^N l_N - \int_{\bar{x}_{n-1}}^x \bar{\rho}(y) dy \right) dx \end{aligned}$$

- From atomization of initial density (31)

$$\begin{aligned}
 & W_{L,1}(\hat{\rho}^N(0), \bar{\rho}) \\
 & \leq \sum_{i=0}^{n-2} \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(\alpha_i^N l_N - \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) dx + \int_{\bar{x}_{n-1}}^{\bar{x}_n} \left(\alpha_{n-1}^N l_N - \int_{\bar{x}_{n-1}}^x \bar{\rho}(y) dy \right) dx \\
 & = \sum_{i=0}^{n-1} \alpha_i^N l_N \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(1 - \frac{1}{\alpha_i^N l_N} \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) dx \\
 & \leq \max_{i=0, \dots, n} \left\{ \alpha_i^N \right\} l_N (\bar{x}_n - \bar{x}_0)
 \end{aligned}$$

- From atomization of initial density (31)

$$\begin{aligned}
 & W_{L,1}(\hat{\rho}^N(0), \bar{\rho}) \\
 & \leq \sum_{i=0}^{n-2} \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(\alpha_i^N l_N - \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) dx + \int_{\bar{x}_{n-1}}^{\bar{x}_n} \left(\alpha_{n-1}^N l_N - \int_{\bar{x}_{n-1}}^x \bar{\rho}(y) dy \right) dx \\
 & = \sum_{i=0}^{n-1} \alpha_i^N l_N \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(1 - \frac{1}{\alpha_i^N l_N} \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) dx \\
 & \leq \max_{i=0, \dots, n} \left\{ \alpha_i^N \right\} l_N (\bar{x}_n - \bar{x}_0)
 \end{aligned}$$

- From (35)-(36), conclude that $(\rho^N(0))_{n \in \mathbb{N}}$ converges to $\bar{\rho}$ in sense of $W_{L,1}$ -Wasserstein distance

- From atomization of initial density (31)

$$\begin{aligned}
 & W_{L,1}(\hat{\rho}^N(0), \bar{\rho}) \\
 & \leq \sum_{i=0}^{n-2} \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(\alpha_i^N l_N - \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) dx + \int_{\bar{x}_{n-1}}^{\bar{x}_n} \left(\alpha_{n-1}^N l_N - \int_{\bar{x}_{n-1}}^x \bar{\rho}(y) dy \right) dx \\
 & = \sum_{i=0}^{n-1} \alpha_i^N l_N \int_{\bar{x}_i}^{\bar{x}_{i+1}} \left(1 - \frac{1}{\alpha_i^N l_N} \int_{\bar{x}_i}^x \bar{\rho}(y) dy \right) dx \\
 & \leq \max_{i=0, \dots, n} \left\{ \alpha_i^N \right\} l_N (\bar{x}_n - \bar{x}_0)
 \end{aligned}$$

- From (35)-(36), conclude that $(\rho^N(0))_{n \in \mathbb{N}}$ converges to $\bar{\rho}$ in sense of $W_{L,1}$ -Wasserstein distance
- Finally generalize convergence to unique entropy solution of conservation law (6)
 $\Rightarrow$ require only minor modifications to arguments in **francesco rigorous 2015**